



SA8253C

1GE+1FE+1POTS



Overview

To deliver triple-play services to the subscriber in Fiber-to-the-Home or Fiber-to-the-Premises application, the GPON RGU (Residential Gateway Unit) **SA8253C** incorporates interoperability, key customers' specific requirements and cost-efficiency.

Equipped with ITU-T G.984 compliant 2.5G Downstream and 1.25G Upstream GPON interface, **SA8253C** supports the full Triple Play of services including voice, video, and high speed internet access service.

Compliant with standard OMCI definition, **SA8253C** is manageable at remote side and supports the full range FCAPS functions including supervision, monitoring and maintenance.



SA8253C Hardware

Interface Description

WAN (Fixed Optical Connector)	SC/APC or SC/UPC
LAN	1*10/100/1000 Base-T with RJ45 connectors 1*10/100 Base-T with RJ45 connectors
Voice	1* FXS voice ports with RJ11 connectors
WPS	1*WPS
Reset	1*Pinhole Reset Button
Power	+12V (external AC/DC adapter)

LED Indicator

Power LOS PON LAN1 LAN2 POTS WPS

GPON features

SFF type laser, SC/APC, or SC/UPC connector

Bosa onboard optical solution

Receiving sensitivity -27dBm (-33dBm optional), and -8dBm overload, Transmitting optical power: 0.5dBm~+4dBm

1.244 Gbps burst mode upstream transmitter; 2.488 Gbps downstream receiver

SA8253C Main Specification

Wavelengths: upstream 1310nm, downstream 1490nm

Ethernet features

1* 10/100/1000 Base-T and 1* 10/100 MDI/MDIX RJ-45 port compliant

IEEE 802.3/802.3u

Hardware-based 10/100/1000, full/half, flow control auto-negotiation

Non-blocking wire-speed reception and transmission Full duplex IEEE 802.3x flow control and half-duplex backpressure flow control

SA8253C Main Specification



Power Supply

Power supply	External AC/DC power adapter 12V 1.5A
Power Consumption	less than 19W

Working Environment

Temperature	-10°C ~ 45°C
Humidity	8%~ 95% relative humidity

Installation

Desk	Desk-top
Wall	Wall-Mounted

SA8253C Software

GPON

ITU-T G.984.X standard Complaint
32 T-CONTs & 256 GEM Ports per devic
Flexible mapping between GEM Ports and T-CONT Support for Multicast GEM Port
AES-128 Decryption with key generation and switching
FEC (Forward Error Correction)
802.1p mapper service profile on U/S
Activation with automatic discovered SN and password in conformance with ITU-T G.984.3



Support Multicast GEM port

Support loop detection

Gateway

Multiple WAN interfaces supporting

WAN Connection: PPPOE, DHCP, Static

Support IPV4/IPV6 dual-stack

Support port forwarding and DHCP server for LAN devices

Support NAT and NAPT

Support ACL (Access Control List)

VPN pass-through PPTP, L2TP, IPSec

Support Firewall

Support ALG, DMZ, DDNS, UTP, UPNP

Ethernet/IP

802.1D bridging

VLAN tagging/detagging per Ethernet port

IP ToS/DSCP to 802.1p mapping

Class of Service based on UNI, VLAN-ID, 802.1p bit, and combination

Marking/remarking of 802.1p



IGMP v2/v3 snooping and IGMP snooping with a proxy report

Broadcast/Multicast rate limiting

VOIP

3-REN

Multiple Codecs: G.711 G.729, G.723.1

Multiple Protocol support: SIP (RFC3261), MEGACO v2 (H.248), SDP (RFC2327), RTP (RFC3550/3551)

T.38 FAX

Support various CLASS services – Caller ID, Call Waiting, Call Forwarding, Call Transfer, Call Toggle, Three-Way Calling, Distinctive Ringing, etc.

Management

Webpage management by default IP address

Remote access by WAN interface through HTTP, HTTPS, Telnet, SSH

Standard-compliant OMCI interface as defined by ITU-T G.984.4 and G.988

Compliant to TR-069, TR-098, TR-104

Support SNMP

Two software hold with integrity checking and automatic rollback